

BÅT

MODELL

R410A
REFRIGERANT



ASB-05A
ASB-09A
ASB-12A
ASB-16A

- Kompakt design
- Vann kjølt
- Kobber-nikkel varmeveksler
- Kan brukes både ved 50 og 60 HZ
- Høy COP
- Korrosjon- og rust beskyttet
- Fastmontert kontroller + fjernkontroll



ASB-12A





MODELL		ASB-05A	ASB-09A	ASB-12A
Kapasitet kjøling / varme	kW	1,1 / 1,4	2,1 / 2,2	3,1 / 3,2
Tilførsel	Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240
SEER / SCOP	-	1,96 / 2,64	2,33 / 2,50	2,82 / 2,91
Lydnivå 1 m	dB(A)	58	58	58
Dimensjon (b x h x d) vekt	mm/kg	285 x 408 x 295 / 25,5	380 x 408 x 310 / 28,0	380 x 420 x 330 / 33,0
Driftstemperatur kjøling / varme	°C	16~43 / -10~30	16~43 / -10~30	16~43 / -10~30

MODEL		ASB-16A		
Kapasitet kjøling / varme	kW	3,2 / 4,0		
Tilførsel	Hz / V	1~ / 50 / 220-240		
SEER / SCOP	-	2,67 / 3,08		
Lydnivå 1 m	ID dB(A)	62		
Dimensjon (b x h x d) vekt	ID mm/kg	450 x 465 x 330 / 37,5		
Driftstemperatur kjøling / varme	°C	16~43 / -10~30		

Contains fluorinated greenhouse gases covered by the Kyoto Protocol. R410A (50% HFC-32, 50% HFC-125), GWP of refrigerant used: 2088.



www.energi-1.no

