

CAMPING AIRCONDITION



R410A
REFRIGERANT

NYTT DESIGN !

NEW

ASV-25AS
ASV-35AS

- Wifi
- Driftstemperatur 4-46 °C
- For tak med tykkelse 30-80 mm
- El. tilførsel 220-240V/50Hz/1fas
- Ultrastynn design på innedel
- Manuell styring og fjernkontroll
- Kraftfull kjøling, varme og avfukting
- Lydsvak





MODELL			ASV-25AS	ASV-35AS	
Kapasitet kjøling / varme	kW		2,5 / 2,2	3,5 / 3,2	
Tilførsel	Hz / V		1~ / 50 / 220-240	1~ / 50 / 220-240	
SEER / SCOP	-		2,34 / 2,24	2,76 / 2,71	
Lydnivå 1m	ID	dB(A)	53 / 48 / 43 / 38	55 / 49 / 44 / 39	
	UD	dB(A)	65 / 55	65 / 55	
Dimensjon (b x h x d) vekt	ID	mm/kg	610 x 49 x 485 / 2,7	610 x 49 x 485 / 2,7	
	UD	mm/kg	1018 x 259 x 650 / 42,5	1018 x 259 x 650 / 42,5	
Driftstemperatur kjøling / varme	°C		18 ~ 43 / 2 ~ 24	18 ~ 43 / 2 ~ 24	

Contains fluorinated greenhouse gases covered by the Kyoto Protocol. R410A (50% HFC-32, 50% HFC-125), GWP of refrigerant used: 2088. Hermetically sealed system.

 **Energi1**
Aircondition og varmepumper
NÆRING OG PRIVAT
www.energi-1.no

 **SINCLAIR**
AIR CONDITIONING