



ECOLOGICAL
KULDEMEDIUM R32

ASF-12BI ASF-36BI
ASF-18BI ASF-42BI
ASF-24BI ASF-48BI
ASF-30BI ASF-60BI

- Autorestart
- Pot free kontakt på / av
- Tillegg I WiFi

ASF-XXBI



ASGE-XXBI-3



ASGE-XXBI



DC INVERTER

MODELL			ASGE-12BI ASF-12BI	ASGE-18BI ASF-18BI	ASGE-24BI ASF-24BI	ASGE-30BI ASF-30BI	ASGE-36BI ASF-36BI
Kapasitet kjøling / varme	kW		3,5 / 4,0	5,0 / 5,5	7,0 / 8,0	8,5 / 8,8	10,0 / 12,0
Tilførsel utedel	Hz / V		1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240
SEER / SCOP	-		6,1 / 4,0	6,1 / 4,0	6,8 / 4,0	6,1 / 4,0	6,1 / 4,0
Energi klasse kjøling / varme	-		A++ / A+	A++ / A+	A++ / A	A++ / A+	A++ / A+
Lydnivå 1m	ID	dB(A)	39/36/32/28	44 / 42 / 39 / 36	45 / 44 / 41 / 38	49 / 47 / 45 / 43	49 / 47 / 45 / 43
Lydnivå utedel 1m	UD	dB(A)	50	50	52	53	55
Dimensjon (b x h x d) vekt	ID	mm/kg	870x665x235 / 25	870x665x235 / 26	1200x665x235 / 31	1200x665x235 / 31	1200x665x235 / 32
	UD	mm/kg	818x596x378 / 37	818x596x378 / 39	892x698x396 / 53	920x790x427 / 60	940x820x530 / 83
Driftstemperatur kjøling / varme	°C		-20~48 / -20~24	-20~48 / -20~24	-20~48 / -20~24	-20~48 / -20~24	-20~48 / -20~24

MODELL			ASGE-36BI-3 ASF-36BI	ASGE-42BI-3 ASF-42BI	ASGE-48BI-3 ASF-48BI	ASGE-60BI-3 ASF-60BI	
Kapasitet kjøling / varme	kW		10,0 / 12,0	12,1 / 13,5	13,4 / 15,5	16,0 / 17,0	
Tilførsel innedel	Hz / V		3~ / 50 / 380-415	3~ / 50 / 380-415	3~ / 50 / 380-415	3~ / 50 / 380-415	
SEER / SCOP	-		6,1 / 4,0	5,8 / 3,8	5,4 / 3,7	6,1 / 4,0	
Energi klasse kjøling / varme	-		A++ / A+	A++ / A	A++ / A+	A++ / A+	
Lydnivå 1m	ID	dB(A)	49 / 47 / 45 / 43	49 / 47 / 44 / 42	52 / 50 / 48 / 44	54 / 53 / 49 / 45	
Lydnivå utedel 1m	UD	dB(A)	55	56	57	57	
Dimensjon (b x h x d) vekt	ID	mm/kg	1200x665x235 / 32	1570x665x235 / 40	1570x665x235 / 42	1570x665x235 / 42	
	UD	mm/kg	940x820x530 / 89	940x820x530 / 95	940x820x530 / 99	900x1345x412 / 112	
Driftstemperatur kjøling / varme	°C		-20~48 / -20~24	-20~48 / -20~24	-20~48 / -20~24	-20~48 / -20~24	

* Tilførsel alle inndeler= 1~ / 50 / 220-240.

Contains fluorinated greenhouse gases covered by the Kyoto Protocol. R32 (single component refrigerant HFC), GWP of refrigerant used: 675.