

UNI SPLITT SERIE



ECOLOGICAL
 RUTBEMIDTUM R32



ASC-12BI ASC-36BI
 ASC-18BI ASC-42BI
 ASC-24BI ASC-48BI
 ASC-30BI ASC-60BI

- Autorestart
- Luftretning 4-veier
- Vannpumpe
- Pot frree på / av
- Tillegg WiFi



ASC-XXBI

ASGE-XXBI-3



ASGE-XXBI



DC INVERTER

MODELL		ASGE-12BI ASC-12BI	ASGE-18BI ASC-18BI	ASGE-24BI ASC-24BI	ASGE-30BI ASC-30BI	ASGE-36BI ASC-36BI
Kapasitet kjøling / varme	kW	3,5 / 4,0	5,0 / 5,5	7,0 / 8,0	8,5 / 8,8	10,0 / 12,0
Tilførsel utedel	Hz / V	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240	1~ / 50 / 220-240
SEER / SCOP	-	3,5 / 4,0	5,9 / 4,0	7,2 / 3,9	6,1 / 4,0	6,1 / 4,0
Energi klasse kjøling / varme	-	A+ / A+	A+ / A	A++ / A	A++ / A+	A++ / A+
Lydnivå innedel 1,4m	dB(A)	39 / 36 / 33	44 / 39 / 36 / 33	43 / 42 / 40 / 39	49 / 47 / 44 / 41	50 / 48 / 46 / 42
Lydnivå utedel 1m	dB(A)	50	50	52	53	55
Dimensjon (b x h x d) vekt	ID	mm/kg	570x265x570 / 17	570x265x570 / 17	840x240x840 / 29	840x240x840 / 31
	UD	mm/kg	818x596x378 / 37	818x596x378 / 39	892x698x396 / 53	920x790x427 / 60
	Panel	mm/kg	620x47,5x620 / 3	620x47,5x620 / 3	950x52x950 / 6	950x52x950 / 6
Driftstøperatur kjøling / varme	°C	-20~48 / -20~24	-20~48 / -20~24	-20~48 / -20~24	-20~48 / -20~24	-20~48 / -20~24

MODELL		ASGE-36BI-3 ASC-36BI	ASGE-42BI-3 ASC-42BI	ASGE-48BI-3 ASC-48BI	ASGE-60BI-3 ASC-60BI	
Kapasitet kjøling / varme	kW	10,0 / 12,0	12,1 / 13,5	13,4 / 15,5	16,0 / 17,0	
Tilførsel utedel	Hz / V	3~ / 50 / 380-415	3~ / 50 / 380-415	3~ / 50 / 380-415	3~ / 50 / 380-415	
SEER / SCOP	-	6,1 / 4,0	6,1 / 3,8	6,1 / 4,0	6,1 / 3,8	
Energi klasse kjøling / varme	-	A++ / A+	A++ / A	A++ / A+	A++ / A	
Lydnivå innedel 1,4m	dB(A)	50 / 48 / 46 / 42	51 / 49 / 46 / 42	52 / 51 / 48 / 45	54 / 52 / 50 / 48	
Lydnivå utedel 1m	dB(A)	55	56	57	57	
Dimensjon (b x h x d) vekt	ID	mm/kg	840x240x840 / 31	840x290x840 / 33	840x290x840 / 36	840x290x840 / 36
	UD	mm/kg	940x820x530 / 89	940x820x530 / 95	940x820x530 / 99	900x1345x412 / 112
	Panel	mm/kg	950x52x950 / 6	950x52x950 / 6	950x52x950 / 6	950x52x950 / 6
Driftstøperatur kjøling / varme	°C	-20~48 / -20~24	-20~48 / -20~24	-20~48 / -20~24	-20~48 / -20~24	

* Tilførsel alle innedeler 1~ / 50 / 220-240

Contains fluorinated greenhouse gases covered by the Kyoto Protocol. R32 (single component refrigerant HFC), GWP of refrigerant used: 675.